

## Freeform Search

---

<b>Database:</b>	US Pre-Grant Publication Full-Text Database US Patents Full-Text Database US OCR Full-Text Database EPO Abstracts Database JPO Abstracts Database Derwent World Patents Index IBM Technical Disclosure Bulletins				
<b>Term:</b>	<input current""="" eddy="" type="text" value="L9 and "/>				
<b>Display:</b>	<input type="text" value="10"/>	<b>Documents in Display Format:</b>	<input type="text" value="1"/>	<b>Starting with Number</b>	<input type="text" value="1"/>
<b>Generate:</b>	<input type="radio"/> Hit List <input checked="" type="radio"/> Hit Count <input type="radio"/> Side by Side <input type="radio"/> Image				

---

  


---

### Search History

---

DATE: Thursday, November 04, 2004 [Printable Copy](#) [Create Case](#)

<u>Set Name</u>	<u>Query</u>	<u>Hit Count</u>	<u>Set Name</u>
side by side			result set
<i>DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ</i>			
<u>L10</u>	L9 and "eddy current"	42	<u>L10</u>
<u>L9</u>	L8 and "inductive"	531	<u>L9</u>
<u>L8</u>	374/\$	33300	<u>L8</u>
<u>L7</u>	L3 and "bimetal coil"	0	<u>L7</u>
<u>L6</u>	L5 and "movement"	248	<u>L6</u>
<u>L5</u>	L4 and "induction"	530	<u>L5</u>
<u>L4</u>	L3 and "coil"	879	<u>L4</u>
<u>L3</u>	(temperature sensor) and (eddy current)	1203	<u>L3</u>
<u>L2</u>	(bimetal coil) and (inductor) and (eddy current)	0	<u>L2</u>
<i>DB=USPT; PLUR=YES; OP=ADJ</i>			
<u>L1</u>	6523427.bn.	1	<u>L1</u>

END OF SEARCH HISTORY

10647926

## Freeform Search

**Database:**

- US Pre-Grant Publication Full-Text Database
- US Patents Full-Text Database
- US OCR Full-Text Database
- EPO Abstracts Database
- JPO Abstracts Database
- Derwent World Patents Index
- IBM Technical Disclosure Bulletins

**Term:** L27 and "temperature sensor"

**Display:** 10  Documents in Display Format:  Starting with Number 1

**Generate:**  Hit List  Hit Count  Side by Side  Image

## Search History

**DATE:** Thursday, November 04, 2004 [Printable Copy](#) [Create Case](#)

<u>Set Name</u>	<u>Query</u>	<u>Hit Count</u>	<u>Set Name</u>
side by side			result set
<i>DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ</i>			
<u>L28</u>	L27 and "temperature sensor"	68	<u>L28</u>
<u>L27</u>	eddy current sensor	1404	<u>L27</u>
<u>L26</u>	L25 and "eddy current"	16	<u>L26</u>
<u>L25</u>	L24 and "coil"	100	<u>L25</u>
<u>L24</u>	inductive displacement sensor	213	<u>L24</u>
<u>L23</u>	induction displacement sensor	15	<u>L23</u>
<u>L22</u>	induction temperature sensor	6	<u>L22</u>
<i>DB=EPAB; PLUR=YES; OP=ADJ</i>			
<u>L21</u>	SU-396220-A.did.	0	<u>L21</u>
<i>DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ</i>			
<u>L20</u>	inductive température sensor	3	<u>L20</u>
<u>L19</u>	L18 and "eddy current"	30	<u>L19</u>
<u>L18</u>	L17 and "temperature sensor"	233	<u>L18</u>
<u>L17</u>	inductive sensor	3883	<u>L17</u>
<u>L16</u>	unductive temperature sensor	0	<u>L16</u>
<i>DB=USPT; PLUR=YES; OP=ADJ</i>			

<u>L15</u>	L14 and "eddy current"	1	<u>L15</u>
<u>L14</u>	5243860.pn.	1	<u>L14</u>
<i>DB=USPT,USOC,EPAB,JPAB,DWPI; PLUR=YES; OP=ADJ</i>			
<u>L13</u>	2341998	13	<u>L13</u>
<i>DB=USPT; PLUR=YES; OP=ADJ</i>			
<u>L12</u>	L11 and "eddy current"	1	<u>L12</u>
<u>L11</u>	5255981.pn.	1	<u>L11</u>
<i>DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ</i>			
<u>L10</u>	L9 and "eddy current"	42	<u>L10</u>
<u>L9</u>	L8 and "inductive"	531	<u>L9</u>
<u>L8</u>	374/\$	33300	<u>L8</u>
<u>L7</u>	L3 and "bimetal coil"	0	<u>L7</u>
<u>L6</u>	L5 and "movement"	248	<u>L6</u>
<u>L5</u>	L4 and "induction"	530	<u>L5</u>
<u>L4</u>	L3 and "coil"	879	<u>L4</u>
<u>L3</u>	(temperature sensor) and (eddy current)	1203	<u>L3</u>
<u>L2</u>	(bimetal coil) and (inductor) and (eddy current)	0	<u>L2</u>
<i>DB=USPT; PLUR=YES; OP=ADJ</i>			
<u>L1</u>	6523427.pn.	1	<u>L1</u>

END OF SEARCH HISTORY